



MICROMARMO PRIMER

Tech Sheets

Rev. 1 – SP119

MICROMARMO PRIMER

1. SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Primer of rough surface adhesion, specific to facilitate the anchoring of plaster on smooth or poorly absorbent supports (tiles, glass, cellular concrete, plasterboard, plaster). It is used as a special adhesive with high adhesion to substrates where normally the plasterwork would have major adhesion problems (eg marble or plaster on plasterboard, gypsum, cellular concrete, ceramic tiles).

2.COMPOSITION

High adhesion terpolymer acrylic, surface tension reducers, quartz granules, and other additives.

3. METHOD OF APPLICATION

MICROMARMO PRIMER is ready to use, needs to be well mixed before use, and applied directly with brush or roller. Before laying mortar or adhesives, wait at least 24 hours. The surfaces must be perfectly cleaned, without the slightest trace of dust. On blunt surfaces, it is necessary to consolidate with a DERASOL H2O diluted 1: 1 with water, and after a minimum of 24 hours minimum, MICROMARMO PRIMER. Avoid applying the product with relative air humidity over 80%); Do not apply on damp surfaces or where infiltrating humidity has been noticed.

4. TECHNICAL DATA

SPECIFIC WEIGHT 1,296 Kg./Lt. +/-5% **VISCOSITY:** tixotropico.

COVERAGE: 0,150-0,200 Lt. Per square meter

DILUTION: ready to use

PACKAGING: Polyethylene containers Lt, 15, Lt 4, Lt 0.750

DRYING: to touch 30', completely 24 hours at 20°C

RE_COATING: 24hours

APPLICTION: Brush, Roller

STORAGE: 36 months in original packing, keep away from temperature changes.

HS-CODE : 32091000

5. ITEM OF SPECIFICATION

Pre-treatment with a rough adhesion promoter of cracking wall surfaces with the application of one coat PRIMER RV type of SPIVER S.r.l ..

...

N.B. The above data may be subject to change. Spiver srl assumes no responsibility for the negative results that depend on applications running outside of its control or due to causes unconnected to the quality of the product

Technical Data Sheet: Micromarmo Primer SP 119. Rev.1 This tab deletes and replaces the previous ones



Atova International

2452 N Harlem, Elmwood Park, IL 60707

Phone: 866-452-9982, Fax:708-452-9982

info@paintandplasters.com www.paintandplasters.com