

Name	URBAN STYLE BALDECOR
Description	Acrylic resin-based product, glossy and pearly version.
Main features	Interior decoration finish.
Baldini Tecnicolor	Possibility to color Urban Style BalDecor with Edilizia colouring pastes and with Baldini Tecnicolor Edilizia Tinting system.
Classification (UNI 8681)	B4.C.O.A.2.FA Finish coat paint in water dispersion, monocomponent, physically drying, glossy or pearly, acrylic.
Surfaces preparations	WALLS NEW WALLS: Ensure that wall is dried and well seasoned. Brush off any non-adherent detritus. Isolate the wall with Fissativo Acrilico. Apply a coat of Synuil Muro paint in the desired shade, then apply BalDecor. PAINTED WALLS: Brush off any non-adherent detritus. Fill any cracks and holes with Stuccotone Paste. Isolate plastered parts with Fissativo Acrilico. Apply one coat of Synuil Muro paint in the desired shade, then apply BalDecor. WOOD NEW WOOD OR PAINTED WOOD WITH ADHERENT SURFACES: Sand the substrate with sand paper. Apply a coat of Solden Plus. Sand the substrate again. Apply one or two coats of Synuil Muro paint in the desired shade, then apply BalDecor. PAINTED WOOD WITH NON-ADHERENT SURFACE: Remove the loose paint with sand paper. Fill any imperfections with Stuccotone Paste. Apply one coat of Solden Plus. Sand the substrate. Apply one coat of Synuil Muro paint in the desired shade, then apply BalDecor. METAL NEW SURFACE: Clean the substrate to remove any grease, then dry it (remove eventual presence of calamine or rust with sand paper). Apply one coat of Noxidine Antiruggine. Apply one coat of Synuil Muro paint in the desired colour, then apply BalDecor. PREVIOUSLY TREATED SURFACE: Use sand paper to remove any rust or flaking paint. Apply a coat of Noxidine Antiruggine. Apply a coat of Synuil Muro paint in the desired shade, then apply BalDecor.
Application Cycle	Coat surface with brush, then work or finish with spatula or other tools according to the chosen effect. More precisely: apply the product on 2-3 sq.m. of surface at a time and work it with the tool. Proceed with successive applications overlapping by 10 to 20 cm to prevent seams from showing. Do not stop application at mid wall, but reach closest corner. Ambient and surface conditions: ambient temperature min. 5°C / max 35°C; ambient relative humidity: < 80%; surface temperature : min 5°C / max 35°; surface moisture: < 10 of relative humidity.
Safety data	<ul style="list-style-type: none">• Keep the tin tightly closed, upside down and protected from frost.• No labelling required• User information is contained in the relevant safety sheet.• Empty containers and containers with traces of dried product film must be disposed of according to local regulations.
Tender Item	Application of Urban Style Baldecor with an average consumption of _____ l per sq. m, to be applied in two coats at a cost of € _____ per sq. m, including materials and labour and excluding scaffoldings and surface dressing.

Specifications and other technical information	Method	Main data at 20°C and 60% relative umidity.
Coat finish and aspect		Glossy , perlescent
Density g/ml	BVL 007 (UNI 8910)	1,010 ÷ 1,050
Viscosity Brookfield cps	BVL 021 (ASTM D 2196)	2500 ÷ 3500
Calculated spreading rate per coat	BVL 052 (ISO 7254)	6 - 8 m ² \ lt
Flash point °C	BVL 046 (UNI 8909)	Not flammable
Solid content % in weight(referred to White)	BVL 027 (UNI 8906)	23 ÷ 29
Shelf life (in cool and dry place)	BVL 064 (UNI 10154)	At least 36 months
Dry tack free hrs	BVL 033	N.A.
Touch dry hrs	BVL 033	2 ÷ 4
Hard dry hrs	BVL 033	24
Dry to recoat hrs	BVL 037	After 12
Exterior \ Interior		NO / YES
Colours		Colour card shades
Binder		Acrilyc
Thinner		Water
Tool cleaner		Water
Applications by brush, cloth, plug, spatula		Ready to use

The above information is based on our best technical and practical knowledge. However, since the actual conditions in which the product is used are beyond our direct control, we provide no guarantee as to the effectiveness of the recommendation and suggestions contained herein . If in doubt, it is advisable to conduct preliminary tests and /or call our technical Service

Atova International

2452 N. Harlem Ave.
 Elmwood Park, IL 60707
 Phone:1-866-452-9982
 Fax:1-708-452-8331
www.paintandplasters.com
techsupport@paintandplasters.com

